

STANDARD FEATURES

- Hydraulic Steering System And Sport Steering Wheel
- Standard Rigging From Factory
- Height Adjustable Steering Wheel
- 12V DC Socket & USB-C Port
- Stainless Steel Gas Springs
- Automatic Bilge Pump
- Master Switch
- Battery Charger (Subject to Country of Delivery)
- Fuel/Water Separator & Canister
- Fuel Sending Unit
- LED Courtesy Lights
- SS LED Navigation Light
- All Around LED Anchor Light
- Stainless Steel Bow Eye
- Bow Step
- Integrated Stainless Steel Bow Rails
- Bow Locker with Cushioned Seating
- Fully Upholstered Seating-Spradling ®
- Under Seat Storage Compartments
- Built-In Cooler with Drain
- SS Cupholders & Plexiglass Windshield
- 3 Stainless Steel Fold Down Cleats
- 3 Stainless Steel Davit Lifting Points
- Molded-In Fiberglass Rear Seat, Console & Seats
- Integrated Aluminum Fuel Tank
- Fresh Water System
- Solid Double Rub Rail
- Sunbathing Bed
- Stainless Steel Tie Down Eyes
- Stainless Steel Tow Rings
- Stern Recessed Foldable Ladder
- 3 Layers Reinforced Seams
- ORCA (CSM) Coated Fabric
- Reinforced ORCA (CSM) Fabric Handles on Tubes
- Owner's Manual
- Maintenance Kit
- Hand Pump

OPTIONAL FEATURES

| | |
|------------------------|--------------------------------------|
| • Flip Up Seat | • Cover |
| • Light Arch | • Chock Set |
| • Bimini Top | • Console Cover |
| • Synthetic Teak Floor | • Lifting Harness |
| • Compass | • Color Boat Customization |
| • Stereo System | • Seadek ® Foam Teak (Grey or Mocca) |
| • VHF Radio | |
| • Rod Holders | |



| SPECIFICATION | IMPERIAL | METRIC |
|---------------------|----------|---------|
| OVERALL LENGTH | 17' | 5.18 M |
| OVERALL BEAM | 8' 1" | 2.46 M |
| INSIDE LENGTH | 13' 1" | 4.00 M |
| INSIDE BEAM | 4' 5" | 1.35 M |
| TUBE DIAMETER | 20" | 0.51 M |
| NUMBER OF CHAMBERS | 5 | 5 |
| PERSON CAPACITY | 10 | 10 |
| WEIGHT | 1250 LBS | 568 KG |
| MAXIMUM HP | 115 HP | 85.8 KW |
| RDC DESIGN CATEGORY | C | C |
| FUEL BUILT-IN TANK | 33 GAL | 125 LT |
| WATER BUILT-IN TANK | 10 GAL | 38 LT |
| SHAFT LENGTH | 20" | 50.8 CM |