STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top of Tube
- SEADEK® EVA FOAM NON-SKID FLOOR
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Hydraulic Steering System
- SS LED Navigation Light
- All Around Anchor Light
- Standard Rigging From Factory
- Aluminum Console with Plexiglass Windshield & Grab Rail
- Leaning Bolster
- Integrated Aluminum Fuel Tank
- Fuel Sending Unit
- Bow Locker
- Hand Pump
- Maintenance Kit

OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Customized Aluminum Consoles & Seats
- Aluminum Jockey Seat
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	18’	5.49 M
OVERALL BEAM	7’ 11”	2.40 M
INSIDE LENGTH	14’ 8”	4.47 M
INSIDE BEAM	4’ 3”	1.30 M
TUBE DIAMETER	21”	0.53 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	15	15
WEIGHT	859 LBS	390 KG
RECOMMENDED HP	90 HP	67 KW
MAXIMUM HP	115 HP	85.8 KW
SHAFT LENGTH	25”	63.5 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	22°	22°
ALUMINUM HULL THICKNESS	0.190 in	4.78 MM
ALUMINUM TRANSOM THICKNESS	0.250 in	6.35 MM
FUEL BUILT-IN TANK * EPA built-in fuel tank 7% capacity reduction approx.	32 GAL	120 LT